

Гидравлические мембранные дозирующие насосы J-TM

Модель	Расход (л/ч)	Давление (МПа)	Диаметр плунжера (мм)	Диапазон маршрута (мм)	Частота (об/мин)	Мощность двигателя (кВт)	Размер						Вес (кг)	
							DN	D	K	d	h1	h2		L
J-TM-23/64	23	64	8	80	90	4	10	95	65	46	303	383	980	500
J-TM-33/64	33	64	10	80	90	4	10	95	65	46	303	383	980	500
J-TM-40/50	40	50	11	80	90	4	10	95	65	46	303	383	980	500
J-TM-60/50	60	50	13	80	90	4	10	95	65	46	303	383	980	500
J-TM-67/40	67	40	14	80	90	4	10	95	65	46	303	383	980	500
J-TM-100/32	100	32	17	80	90	4	10	95	65	46	303	383	980	500
J-TM-110/32	110	32	18	80	90	4	16	105	75	60	214	254	980	500
J-TM-160/25	160	25	22	80	90	5.5	16	105	75	60	214	254	980	500
J-TM-180/25	180	25	23	80	90	5.5	16	105	75	60	214	254	980	500
J-TM-270/20	270	20	28	80	90	5.5	16	105	75	60	214	254	980	500
J-TM-290/20	290	20	29	80	90	5.5	20	105	75	60	214	254	980	500
J-TM-430/16	430	16	36	80	90	5.5	20	105	75	60	214	254	980	500
J-TM-450/16	450	16	36	80	90	5.5	20	105	75	60	214	254	980	500
J-TM-680/10	680	10	45	80	90	5.5	20	105	75	60	214	254	980	500
J-TM-800/10	800	10	49	80	90	5.5	25	115	85	65	290	320	980	500
J-TM-1200/8	1200	8	59	80	90	5.5	25	115	85	65	290	320	980	500
J-TM-1080 / 6.4	1080	6.4	56	80	90	5.5	25	115	85	65	290	320	980	500
J-TM-1600 / 6.4	1600	6.4	69	80	90	5.5	25	115	85	65	290	320	980	500
J-TM-1460 / 4.0	1460	4.0	66	80	90	5.5	35	135	96	75	290	320	980	500
J-TM-2200 / 2.5	2200	2,5	81	80	90	5.5	35	135	96	75	290	320	980	500

J-TM-1850 / 1.6	1850	1.6	74	80	90	5.5	35	135	96	75	290	320	1000	500
J-TM-2750 / 1.0	2750	1.0	90	80	90	5.5	40	150	110	84	235	265	1000	500
J-TM-2250 / 0.8	2250	0,8	81	80	90	5.5	40	150	110	84	235	265	1000	500
J-TM-3300 / 0.8	3300	0,8	99	80	90	5.5	50	160	125	108	245	275	1000	500
J-TM-5000 / 0,5	5000	0,5	121	80	90	5.5	80	195	160	135	730	670	1000	500
J-TM-7000 / 0,5	7000	0,5	144	80	90	5.5	80	195	160	135	730	670	1000	500