

Плунжерные насосы-дозаторы с дуплексными головками 2JT

Модель	Расход (л/ч)	Давление (МПа)	Диаметр плунжера (мм)	Диапазон маршрута (мм)	Частота (об/мин)	Мощность двигателя (кВт)	Размер						Вес (кг)	
							DN	D	K	d	h1	h2		L
2JT-52/64	52	64	12	80	90	4	8	95	65	46	189	189	1250	750
2JT-78/64	78	64	15	80	90	4	8	95	65	46	189	189	1250	750
2JT-92/50	92	50	16	80	90	4	8	95	65	46	189	189	1250	750
2JT-138/50	138	50	20	80	90	4	8	95	65	46	189	189	1250	750
2JT-152/40	152	40	21	80	90	4	8	95	65	46	189	189	1250	750
2JT-228/40	228	40	26	80	90	4	8	95	65	46	189	189	1250	750
2JT-240/32	240	32	27	80	90	5.5	12	105	85	56	189	189	1250	750
2JT-360/32	360	32	33	80	90	5.5	12	105	85	56	189	189	1250	750
2JT-392/25	392	25	34	80	90	5.5	12	105	85	56	189	189	1250	750
2JT-588/25	588	25	42	80	90	5.5	12	105	85	56	189	189	1250	750
2JT-610/20	610	20	42	80	90	5.5	16	115	85	65	194	194	1300	750
2JT-900/20	900	20	52	80	90	5.5	16	115	85	65	194	194	1300	750
2JT-1016/16	1016	16	55	80	90	5.5	16	115	85	65	194	194	1300	750
2JT-1500/16	1500	16	67	80	90	5.5	16	115	85	65	194	194	1300	750
2JT-1666/10	1666	10	70	80	90	5.5	26	125	98	75	200	200	1350	750
2JT-2500/10	2500	10	86	80	90	5.5	26	125	98	75	200	200	1350	750
2JT-2288/8	2288	8	82	80	90	5.5	26	125	98	75	200	200	1350	750
2JT-3432/8	3432	8	101	80	90	5.5	26	125	98	75	200	200	1350	750
2JT-3100 / 6.4	3100	6.4	96	80	90	5.5	35	125	98	75	200	200	1350	750
2JT-4650 / 4.0	4650	4.0	117	80	90	5.5	35	125	98	75	200	200	1350	750

2JT-4000 / 2.5	4000	2,5	109	80	90	5.5	35	125	98	75	200	200	1350	750
2JT-6000 / 1.6	6000	1.6	133	80	90	5.5	40	145	110	85	235	235	1350	750
2JT-9000 / 1.6	9000	1.6	163	80	90	5.5	40	145	110	85	235	235	1350	750
2JT-7320 / 1.0	7320	1.0	147	80	90	5.5	80	195	160	135	270	270	1350	750
2JT-11000 / 1.0	11000	1.0	180	80	90	5.5	80	195	160	135	270	270	1350	750
2JT-15500 / 0.5	15500	0,5	214	80	90	5.5	80	195	160	135	270	270	1350	750